



VIDAFLEX 942

Composition

VIDAFLEX 942: Braided "E"-glass sleeving coated with acrylic resin.

VIDAFLEX 942 insulating sleeveings are compliant to the requirements of the directive 2002/95/EC (RoHS).

The acrylic resin coating gives the sleeveings an excellent flexibility allied to high abrasion resistance and mechanical strength.

Max. short term temperature: 200°C.

Application

Protection and insulation of leads and wiring harness in household appliances, lamps and vehicles.

Insulation of the internal wiring of all types electrical machines.

Thermal Class 155 (Class F) according to IEC 60085

Bore size (mm)	Nom. wall thickness (mm)	Weight approx. (g/m)	Breakthrough voltage at 20°C (kV)
1,0 ± 0,25	0,35	4	≥ 3,0
2,0 ± 0,25	0,35	5	≥ 3,0
3,0 ± 0,5	0,40	7	≥ 3,0
4,0 ± 0,5	0,45	10	≥ 3,0
5,0 ± 0,5	0,50	13	≥ 3,0
6,0 ± 0,5	0,50	16	≥ 3,0
7,0 ± 0,5	0,65	19	≥ 3,0
8,0 ± 0,5	0,65	27	≥ 3,0
10,0 ± 0,5	0,65	36	≥ 3,0
12,0 ± 1,0	0,70	40	≥ 3,0
14,0 ± 1,0	0,70	45	≥ 3,0
16,0 ± 1,0	0,70	55	≥ 3,0
20,0 ± 1,0	0,90	79	≥ 3,0
25,0 ± 1,0	0,90	124	≥ 3,0

Measurement according to EN 60684-2

Availability	
Standard roll length	250, 100, 50 and 25 m spools dependent on bore size. Cut to length on request
Colour	Black, white, red, green, yellow, blue